


PLAN VIEW



SECTION VIEW

2000 GALLON SEPTIC TANK H-20

NOTES:

1. TOP THICKNESS 1" REINF. WITH #4 REBAR @ 6" O.C. BOTH WAYS
2. BOTTOM THICKNESS 1" REINF. WITH #4 REBAR @ 6" O.C. BOTH WAYS
3. WALL THICKNESS 6" REINF. WITH 6X6 NO. 10 WELDED WIRE MESH
4. TONGUE AND GROOVE JOINT SEALED WITH BUTYL RESIN.
5. ALL CONCRETE F_c 4000 PSI @ 28 DAYS.
6. ALL REBAR ASTM A615 GRADE 60, 1" MIN. COVER.
7. APPROXIMATE WEIGHT 28,000 LBS
8. OPTIONAL BAFFLE WALL FOR MULTI COMPARTMENT TANKS.
9. MAXIMUM DEPTH OF SOIL COVER ABOVE TANK IS 5'-0"

WACHUSETT PRECAST, INC.

14 PRATTS JCT. RD.
P.O. BOX 901
STERLING, MA. 01564
1-800-244-1544

PHONE: 978-422-3311
FAX: 978-422-8818
EMAIL: WPRECAST@AOL.COM
WEB: WACHUSETTPRECAST.COM

2000 GALLON SEPTIC TANK H-20

NOT TO SCALE